



50 Kw Perkins Diesel Generator With Water Cooling System ISO9001 Approved

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO9001
- Model Number: DE-P10~P72
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: 50 Kw Perkins Diesel Generator
- Cooling Method: Water-Cooling System
- Engine Brand: Perkins
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **50 Kw Perkins Diesel Generator ,
50 Kw Perkins Generator ,
Perkins Diesel Generator 50Kw**

for more products please visit us on dellentpower.com

CE Perkins Diesel Generator about 50kW.

At our Perkins generator dealership, we understand the importance of quality and reliability when it comes to power generation. That's why we only offer the best generators from Perkins , a leading manufacturer of power equipment. At our Perkins generator dealership, we understand the importance of quality and reliability when it comes to power generation. That's why we only offer the best generators from Perkins , a leading manufacturer of power equipment.

. PRODUCT

50 Hz		60 Hz		TECHNICAL DATA		PERKINS WATER-COOLED Series Diesel Generator Sets									
Generator Performance				Engine Performance				Dimension(L×W×H)							
Generator Model	Prime Power kW	Standby Power kVA	Engine model	Speed rpm	Prime power kW	Fuel Cons. (100% Load) L/h	Cylinder- Bore×Stroke mm	Displace- ment L	Open Type	Silent Type					
DE-P10	7.2	9	8	10	403D-11G	1500	8.6	2.6	3L-77×81	1.131	115×74×99	180×84×110			
DE-P14	10	12.5	11	14	403A-15G1	1500	12.2	3.7	3L-84×90	1.496	115×74×99	180×84×110			
DE-P17	12	15	13.2	16.5	403A-15G2	1500	14	5	3L-84×90	1.496	115×74×99	180×84×110			
DE-P22	16	20	17.6	22	404A-22G1	1500	18.7	5.3	4L-84×100	2.216	127×74×101	180×84×110			
DE-P30	22	27.5	24	30	404D-22TG	1500	25.2	7.1	4L-84×100	2.216	136×74×101	180×84×110			
DE-P33	24	30	26.4	33	1103A-33G	1500	28.2	7.2	3L-105×127	3.3	152×80×122	230×102×128			
DE-P50	36	45	40	50	1103A-33TG1	1500	42.2	10.8	3L-105×127	3.3	161×80×122	230×102×128			
DE-P66	48	60	52.8	66	1103A-33TG2	1500	55	14.6	3L-105×127	3.3	169×80×122	230×102×128			
DE-P72	52	65	57.6	72	1104A-44TG1	1500	59.6	14.8	4L-105×127	4.4	181×80×124	240×102×128			
DE-P88	64	80	70.4	88	1104A-44TG2	1500	73.4	18.7	4L-105×127	4.4	185×80×124	240×102×128			
DE-P110	80	100	88	110	1104C-44TAG2	1500	93.6	22.6	4L-105×127	4.41	188×85×124	272×108×170			
DE-P150	108	135	120	150	1106A-70TG1	1500	122.7	30.2	6L-105×135	7.01	224×90×141	330×110×170			
DE-P165	120	150	132	165	1106A-70TAG2	1500	136	33.4	6L-105×135	7.01	224×90×141	330×110×170			
DE-P200	144	180	160	200	1106A-70TAG3	1500	163.9	41.6	6L-105×135	7.01	230×90×141	340×110×170			
DE-P220	160	200	176	220	1106A-70TAG4	1500	178.9	45.8	6L-105×135	7.01	235×90×141	340×110×170			
DE-P250	180	225	200	250	1506A-E88TAG2	1500	204	51	6L-112×149	8.8	262×110×162	360×130×190			
DE-P275	200	250	220	275	1506A-E88TAG3	1500	222	56	6L-112×149	8.8	262×110×162	360×130×190			
DE-P300	220	275	240	300	1506A-E88TAG4	1500	244	60	6L-112×149	8.8	273×110×162	380×130×190			
DE-P330	240	300	264	330	1506A-E88TAG5	1500	267	65	6L-112×149	8.8	273×110×162	380×130×190			
DE-P385	280	350	308	385	2206C-E13TAG2	1500	324	75	6L-130×157	12.5	299×120×185	420×140×223			
DE-P450	320	400	360	450	2206C-E13TAG3	1500	368	85	6L-130×157	12.5	308×120×185	430×140×223			
DE-P500	360	450	400	500	2506C-E15TAG1	1500	412	99	6L-137×171	15.2	345×120×198	470×160×223			
DE-P550	400	500	440	550	2506C-E15TAG2	1500	451	106	6L-137×171	15.2	345×120×198	470×160×223			
DE-P680	480	600	528	660	2806C-E18TAG1A	1500	532	129	6L-145×183	18.1	335×154×202	500×180×253			
DE-P720	520	650	576	720	2806A-E18TAG2	1500	584	132	6L-145×183	18.1	341×154×202	500×180×253			
DE-P825	600	750	660	825	4006-23TAG2A	1500	658	157	6L-160×190	22.921	402×171×221	580×200×253			
DE-P880	640	800	704	880	4006-23TAG3A	1500	705	172	6L-160×190	22.921	402×171×221	580×200×253			
DE-P1000	728	900	800	1000	4008TAG1A	1500	805	195	8L-160×190	30.561	470×205×235	680×228×256			
DE-P1125	820	1025	900	1125	4008TAG2A	1500	899	215	8L-160×190	30.561	470×205×235	680×228×256			
DE-P1375	1000	1250	1100	1375	4012-46TWG2A	1500	1113	259	12V-160×190	45.842	485×205×252	40 feet high container			
DE-P1650	1200	1500	1320	1650	4012-46TAG2A	1500	1331	310	12V-160×190	45.842	485×205×252				
DE-P1875	1360	1700	1500	1875	4012-46TAG3A	1500	1500	370	12V-160×190	45.842	497×205×252				
DE-P2000	1480	1850	1600	2000	4016-61TRG1	1500	1648	371	16V-160×190	61.123	634×220×268				
DE-P2200	1600	2000	1760	2200	4016-61TRG2	1500	1774	405	16V-160×190	61.123	624×220×268				
DE-P2500	1800	2250	2000	2500	4016-61TRG3	1500	1975	470	16V-160×190	61.123	625×220×268				
DE-P13	9	11.25	10	12.5	403D-11G	1800	10.7	3	3L-77×81	1.131	115×74×99	180×84×110			
DE-P17	12	15	13.2	16.5	403D-15G	1800	14.7	4.27	3L-84×90	1.496	115×74×99	180×84×110			
DE-P20	14.4	18	16	20	403A-15G2	1800	16	5	3L-84×90	1.496	115×74×99	180×84×110			
DE-P28	20	25	22	27.5	404D-22G	1800	22	6.2	4L-84×100	2.216	127×74×101	180×84×110			
DE-P33	24	30	26.4	33	404D-22TG	1800	30.3	8.3	4L-84×100	2.216	136×74×101	180×84×110			
DE-P39	28	35	30.8	38.5	1103A-33G	1800	33.2	8.6	3L-105×127	3.3	152×80×122	230×102×128			
DE-P60	43	54	48	60	1103A-33TG1	1800	50.5	12.9	3L-105×127	3.3	161×80×122	230×102×128			
DE-P75	54	67.5	60	75	1103A-33TG2	1800	63.3	16.6	3L-105×127	3.3	169×80×122	230×102×128			
DE-P83	60	75	66	82.5	1104A-44TG1	1800	70.7	17.7	4L-105×127	4.4	181×80×124	240×102×128			
DE-P103	75	93.75	82.5	103	1104A-44TG2	1800	84.5	22.3	4L-105×127	4.4	185×80×124	240×102×128			
DE-P125	90	112.5	100	125	1104C-44TAG2	1800	106.8	26.9	4L-105×127	4.41	188×85×124	272×108×170			
DE-P165	120	150	132	165	1106A-70TG1	1800	140.5	35.2	6L-105×135	7.01	224×90×141	330×110×170			
DE-P188	135	169	150	187.5	1106A-70TAG2	1800	155	38.2	6L-105×135	7.01	224×90×141	330×110×170			
DE-P220	160	200	176	220	1106A-70TAG3	1800	180.5	46.4	6L-105×135	7.01	230×90×141	340×110×170			
DE-P270	196	245	216	270	1506A-E88TAG2	1800	218	56	6L-112×149	8.8	262×110×162	360×130×190			
DE-P310	225	281	248	310	1506A-E88TAG3	1800	250	63	6L-112×149	8.8	262×110×162	360×130×190			
DE-P385	280	350	308	385	1506A-E88TAG5	1800	300	77	6L-112×149	8.8	273×110×162	380×130×190			
DE-P440	320	400	352	440	2206A-E13TAG2	1800	373	81	6L-130×157	12.5	299×120×185	420×140×223			
DE-P550	400	500	440	550	2506C-E15TAG1	1800	453	106	6L-137×171	15.2	345×120×198	470×160×223			
DE-P688	500	625	550	687.5	2806C-E18TAG1A	1800	568	130	6L-145×183	18.1	335×154×202	500×180×253			
DE-P825	600	750	660	825	4006-23TAG2A	1800	684	177	6L-160×190	22.921	402×171×221	580×200×253			
DE-P935	680	850	748	935	4006-23TAG3A	1800	759	200	6L-160×190	22.921	402×171×221	580×200×253			
DE-P1100	800	1000	880	1100	4008TAG2	1800	898	224	8L-160×190	30.561	470×205×235	680×228×256			
DE-P1375	1000	1250	1100	1375	4012-46TWG2A	1800	1113	266	12V-160×190	45.842	485×205×252	40 feet high container			
DE-P1650	1200	1500	1320	1650	4012-46TAG2A	1800	1332	319	12V-160×190	45.842	485×205×252				
DE-P1875	1360	1700	1500	1875	4012-46TAG3A	1800	1500	361	12V-160×190	45.842	497×205×252				

Http www.dellent.com | 03

. Why Choose Us:

Dedicated

We are DEDICATED to meet Customers' need.

Enthusiasm

We respond to our Customers' ENTHUSIASM

Loyalty

We cherish our Customers' LOYALTY

Luxury

We aim to establish our own LUXURY brand

Efficient

We offer our EFFICIENT service

Newest

We adopt NEWEST technologies for products

Trust

We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDE CITY,FUJIAN.CHINA

